

| Flight | Destination         | Time    | Gate       |
|--------|---------------------|---------|------------|
| 32032  | Singapore           | 1100 00 | On to Gate |
| LN6789 | Singapore Frankfurt | 1100 52 | On to Gate |
| QF43   | Auckland            | 1100 21 |            |
| AA7577 | Auckland            | 1100 37 |            |
| BB142  | Noumea              | 1100 25 |            |
| QP282  | Noumea              | 1100 25 |            |
| SP6208 | Melbourne           | 1100 01 |            |
| JL779  | Kansai - Osaka      | 1100 01 |            |
| QF372  | Kansai - Osaka      | 1100 01 |            |

| Flight       | Destination          | Time    | Gate |
|--------------|----------------------|---------|------|
| DL100        | Atlanta              | 1200 04 |      |
| QF201        | Naiti                | 1200 32 |      |
| QF201        | Los Angeles          | 1200 32 |      |
| AA7502       | Los Angeles          | 1200 32 |      |
| UNITED UA860 | Los Angeles New York | 1200 32 |      |
| QF73         | San Francisco        | 1200 43 |      |
| AA7581       | San Francisco        | 1200 43 |      |
| QF122        | Kuala Lumpur         | 1200 55 |      |
| QF122        | Kuala Lumpur         | 1200 55 |      |
| QF127        | Hong Kong            | 1200 55 |      |

Duty free shopping closes 20 minutes before departure

10:36

TO GATES



# Interactive Touchscreen Kiosk

**A**BI's interactive kiosks use the latest IR PCB technology for a very fast response to finger touch. For users of Windows 7, and Windows 8, connection is "plug-n-play" - custom software drivers are not required. The touch screens offer dual touch operation, compatible with Windows 7 and 8 programs, as well as Gesture Control (Zoom, Page scroll).

The Kiosk is supplied with touch technology PCB, with full length safety glass front panel. Safety and security have been built into the design. The Kiosk can be bolted down and the two access panels have a master key to operate both doors.

The NEC MultiSync® V Series is one of the first public displays to feature a professional LCD panel with Edge LED Backlights and has a commercial 3 year warranty.

**Features:**

- Finger Touch operation
- Windows 7 & 8 "plug n play"
- Dual touch and Gesture operation
- Full length 5mm safety glass front
- Available as 42" and 55" standard sizes
- Simple internal connection panel
- NEC OPS Core i5 slot-in PC available as optional extra



TSK142 - 42"



TSK155 - 55"



A Brighter Image Pty Ltd  
 T: 02 9938 6866  
 E: info@abimage.com.au





|                            | 42" TSK142                           | 55" TSK155                           |
|----------------------------|--------------------------------------|--------------------------------------|
| <b>Touch Technology:</b>   |                                      |                                      |
| Technology                 | InfraRed                             | InfraRed                             |
| Resolution (Interpolation) | 4096 x 4096                          | 4096 x 4096                          |
| Linearity Error            | 1.5mm                                | 1.5mm                                |
| Response Speed             | <20ms                                | <20ms                                |
| Tracking Speed             | Approx 100 points per second         | Approx 100 points per second         |
| Input Method               | Finger, stylus or opaque object      | Finger, stylus or opaque object      |
| Touch Times                | Unlimited                            | Unlimited                            |
| Touch Advance Force        | No minimum activation force required | No minimum activation force required |
| Minimum Touch Object Size  | 5mm                                  | 5mm                                  |
| Interface                  | USB                                  | USB                                  |

| <b>Kiosk Cabinet</b>  |   |  |
|-----------------------|---|--|
| LCD Glass Cover       | 5mm Hardened Safety Glass   | 5mm Hardened Safety Glass  |
| Operating Temperature | -20°C to 39°C   | -20°C to 39°C  |
| Operating Humidity    | 90% (non condensing at max 40°C)  | 90% (non condensing at max 40°C)                                       |
| Cooling               | 3 x motor fans plus rear vents  | 3 x motor fans plus rear vents   |
| Finish                | FRONT: Full length glass panel  | FRONT: Full length glass panel   |
|                       | SIDE UPRIGHTS: Anodised silver  | SIDE UPRIGHTS: Anodised silver   |
|                       | BACK: Black powdercoat  | BACK: Black powdercoat   |
| Dimensions:           | Kiosk: (42")1900H x 690W x 165D mm  | Kiosk: (55")1900H x 860W x 165D mm                                     |
|                       | Base: 900W x 450D mm  | Base: 900W x 450D mm   |
| Weight:               | 76 kg (42")   | 86 kg (55")  |
| Connectors:           | 42"   | 55"  |
| Input Video Analogue  | 1 x D-sub 15 pin; Composite (BNC)   | 1xD-sub15pin; Composite(BNC); RGBHV for PC & Component/Composite (BNC) |
| Input Video Digital   | 1xDVI-D(with HDCP); 1xHDMI 1.3(with HDCP); 1xDisplayPort(with HDCP)                               | 1 x DVI-D (with HDCP); 1 x HDMI 1.3; 1 x DisplayPort                   |
| Input Audio Analogue  | 1 x 3.5 mm jack   | 1 x 3.5 mm jack  |
| Input Audio Digital   | Display Port; 1x HDMI   | Display Port; 1x HDMI  |
| Input Control         | LAN 100Mbit; remote control wire (3,5mm jack); RS232  | LAN 100Mbit; remote control wire (3,5mm jack); RS232                   |
| Output Video Digital  | DVI-D   | DVI-D  |
| Output Audio Analogue | 3.5mm jack  | 3.5mm jack   |
| Output Control        | RS232   | RS232  |
| Remote Control        | LAN with SNMP; RS-232C, Input and Output; Remote Control IR (internal/external [optional] sensor) |  |

| <b>Panel Specifications</b> |                        |                        |
|-----------------------------|------------------------|------------------------|
|                             | NECV423                | NECV552                |
| Resolution:                 | 1920 x 1080, max 1080p | 1920 x 1080, max 1080p |
| Format:                     | 16:9                   | 16:9                   |
| Warranty:                   | 3 years                | 3 years                |
| Response Time:              | < 5ms                  | < 5ms                  |
| Viewing Angle:              | 176°                   | 176°                   |
| Brightness                  | 500 cd/m <sup>2</sup>  | 500 cd/m <sup>2</sup>  |
| Tuner                       | High Definition        | High Definition        |
| Speakers                    | 2 x 10W                | 2 x 10W                |
| Power Input:                | 100-240V AC 50/60Hz    | 100-240V AC 50/60Hz    |

